Appl.No. 10/533,329

Amdt.dated September 28, 2009

Reply to Office action of April 28, 2009

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

Claim 1 (previously submitted) A proportioner for dispensing plural component materials, said

proportioner comprising:

A variable speed electric motor having a shaft and first and second ends, said shaft

extending from each of said ends;

a first reciprocating piston pump attached to said first motor end, said pump being

connected to a source of a first material and having an output which has a first

pressure;

a second reciprocating piston pump attached to said second motor end, said pump being

connected to a source of a second material and having an output which has a

second pressure, said pumps simultaneously pumping said materials to an

applicator without passing through another pump; and

a controller with provision for a user-selectable pressure setpoint, said controller

continually comparing said first and second pressures and regulating the higher of

said pressures to said setpoint, said first and second pumps being the only pumps

between said material sources and said outputs.

-2-

Appl.No. 10/533,329 Amdt.dated September 28, 2009

Reply to Office action of April 28, 2009

Claim 2 (previously submitted) A proportioner for dispensing plural component materials, said

proportioner comprising:

a variable speed electric motor having first and second ends;

a first reciprocating piston pump attached to said first motor end, said pump being

connected to a source of a first material and having an output which has a first

positive pressure;

a second reciprocating piston pump attached to said second motor end, said pump being

connected to a source of a second material and having an output which has a

second positive pressure, said pumps simultaneously pumping said materials to an

applicator without passing through another pump; and

a controller with provision for a user-selectable pressure setpoint, said controller

continually monitoring said first and second pressures and providing an alarm in

the event one of said pressures falls to a predetermined percentage of said

setpoint.

-3-